



 • •

.



WARRANTY:

2 years

APPLICATIONS AND INSTALLATION:


- To be used in conjunction with internal grilles, and ducting (not inluded)
- May be mounted in either the wall or ceiling space
- Suitable for single room applications including:
 Bathrooms and powder rooms
 - Portable buildings and classrooms
 - Utility rooms
 - Heat transfer
 - Sub-floor ventilation
- Works with short ducting lengths (up to 3m)
- It is recommended that this product be installed by an industry professional (electrician or airconditioning installer)


BENEFITS:

.

- Low wattage motors
- Easy to install
- Can be used with rigid or flexible ducting
- Compact
- Quiet operation
- Ideal solution for heat transfer systems
- Comes in metal or technopolymer

APPLICATIONS:





Wall

SPECIFICATIONS:


Model	Item Code	Volume m³/h (maximum)	Volume L/s (maximum)	Pressure (maximum)	Wattage	Noise dB(A)*	Protection
TUBO 100 Metal	2TU1001	80	22	27	14	38	IXP2
TUBO 120 Metal	2TU1201	150	42	35	18	44	IXP2
TUBO 150 Metal	2TU1506	300	83	75	50	51	IXP2
TUBO 100 TP	2TU1011	90	25	25	14	38	IXP2
TUBO 120 TP	2TU1020	180	50	36	18	44	IXP2
TUBO 150 TP	2TU1501	320	89	69	40	51	IXP2
TUBO 150 TP (Ball bearing)	2TU1509	320	89	69	40	51	IXP2

TP – Technopolymer


* Measured at 3 metres


DIN

Model	Α	BØ	Kg
TUBO 100 Metal	100	100	0.6
TUBO 120 Metal	100	119	0.8
TUBO 150 Metal	125	150	1.2
TUBO 100 TP	92	97	0.4
TUBO 120 TP	97	119	0.6
TUBO 150 TP	125	151	0.8



PERFORMANCE:





MENSIONS:		
odel	Α	
BO 100 Metal	100	

I.